

Speed controller, input by climate computer



Specifications

Туре	SC40/80
Brand	Hortimat
Code	25440
Suitable for	Maximum of 5 fans and/or 10 Ampere
Maximum load	4A or 8A depending on model
Control by	0-10Vdc or potention rotary switch
Switch on/off	Including
Control	Min, max and soft
10V Output Load	Max 25 mA

25440-V22111001-EN

Renewed Quality Machines and Materials





24V Output Load	Max 200 mA
Operating Temperature	0-50°C
Power supply	230 V, 1 phase, zero + earth, 50 Hz

The speed controller controls the motor speed with a signal 0-10VDc/10-0Vdc or 4-25mA/25-4mA. The controller incorporate luminous ON/OFF switch, internal minimum and maximum speed adjust, fan stop set point, fuse protection and sealed box (IP54).

These controllers comply with following mentioned European norms:

EMC89/336/CEE modified by 92/31/CEE and low voltage norm 72/23/CEE

EMC filter according to EN55014 standard, RoHS compliant.

Hortimat customizing work

Hortimat can design the offered machine to exact the customer requirements. Optionally we constructively adjust the machine or we install new operating systems. We also deliver tailor made solutions in the form of logistic conveyor belt systems and we think along with the customer for custom made solutions.

Why Hortimat

- Adapting / modifying of used machines to desired specifications of the customer
- Applying of new 2022 operating systems on used machines
- New Hortimat range of products
- Service and warranty by own technical specialists
- Solid revision; guarantees a long lifetime
- Individual advice about logistics matters, such as: grading machines, processing areas